

TA-F7/TA-F7B

*UK Model
AEP Model*

*TA-F7: silver panel
TA-F7B: black panel*



TA-F7

INTEGRATED STEREO AMPLIFIER

SPECIFICATIONS

GENERAL

Power Requirements: 220V, 50/60 Hz (AEP model)
240V, 50/60 Hz (UK model)

Power Consumption: 400W (AEP model)
410W (UK model)

Dimensions: Approx. 430 (w) x 170 (h) x 420 (d) mm
17 (w) x 6³/₄ (h) x 16⁵/₈ (d) inches
Including projecting parts and controls

Weight: Approx. 20.3 kg, 44 lb 12 oz (net)
Approx. 24.3 kg, 53 lb 9 oz (with shipping carton)

Frequency Response: PHONO 1, 2 RIAA equalization curve ± 0.2 dB
TUNER }
AUX 1, 2 } 5–100,000 Hz ± 1 dB
TAPE 1, 2 }

Tone Controls: BASS ± 10 dB at 30 Hz (TURNOVER
FREQ 150 Hz)
 ± 10 dB at 60 Hz (TURNOVER
FREQ 300 Hz)
TREBLE ± 10 dB at 20 kHz (TURNOVER
FREQ 4 kHz)
 ± 10 dB at 40 kHz (TURNOVER
FREQ 8 kHz)

PREAMPLIFIER SECTION


Harmonic Distortion: Less than 0.015% at rated output
(AEP model)
Less than 0.015% at 1W (UK model)

IM Distortion: Less than 0.015% at rated output
(AEP model)
(60Hz: 7 kHz = 4:1)
Less than 0.015% at 1W (UK model)

Filters: LOW 12 dB/oct. below 30 Hz
HIGH 12 dB/oct. above 9 kHz

— Continued on next page —

SAFETY-RELATED COMPONENT WARNING!!

COMPONENTS IDENTIFIED BY SHADING AND  MARK ON THE SCHEMATIC DIAGRAMS, EXPLODED VIEWS AND IN THE PARTS LIST ARE CRITICAL TO SAFE OPERATION. REPLACE THESE COMPONENTS WITH SONY PARTS WHOSE PART NUMBERS APPEAR AS SHOWN IN THIS MANUAL OR IN SUPPLEMENTS PUBLISHED BY SONY.

SONY[®]

SERVICE MANUAL

TA-F7/TA-F7B

Inputs:

	Sensitivity	Impedance	Maximum Input Capability (THD 0.015% at 1 kHz)	S/N (weighting network, input level)
PHONO 1 PHONO 2	2.5 mV (-50 dB)	50 k Ω	250 mV (-10 dB)	75 dB (A, 2.5 mV)
TUNER AUX 1, 2 TAPE 1, 2	150 mV (-14.5 dB)	50 k Ω	—	95 dB (A, 150 mV)

Outputs:

	Output Level	Impedance
REC OUT 1,2	150 mV	10 k Ω
PRE OUTPUT	1 V	1.5 k Ω

POWER AMPLIFIER SECTION

Continuous RMS Power Output: Both channels driven simultaneously
(rated output) At 20–20,000 Hz
(Less than 0.015% harmonic distortion) 70 + 70W (8 Ω)
According to DIN 45500
70 + 70W (8 Ω)

Power Bandwidth: 5–40,000 Hz, IHF (8 Ω , 0.015 THD)

Damping Factor: 60 (8 Ω , 1 kHz)

Harmonic Distortion: Less than 0.015% at rated output
Less than 0.015% at 1W output

IM Distortion: Less than 0.015% at rated output
(60 Hz: 7 kHz = 4: 1) Less than 0.015% at 1W output

Frequency Response: dc–100,000 Hz ± 1 dB (1W)

S/N Ratio: Greater than 110 dB, short-circuited input

Residual Noise: Less than 0.12 mV

Inputs: POWER INPUT
Sensitivity 1V (for rated output)
Impedance 100 k Ω

Outputs: SPEAKER A, B
Accept speakers of 8 Ω or more
HEADPHONES
Accepts low- and high-impedance stereo headphones

0 dB = 0.775 V

MODEL IDENTIFICATION

— Specification Label —

UK model

SONY®	INTEGRATED STEREO AMPLIFIER MODEL NO. TA-F7 AC 240V ~ 50/60Hz 410W SERIAL NO.
MADE IN JAPAN	

AEP model

SONY®	INTEGRATED STEREO AMPLIFIER MODEL NO. TA-F7 AC 220V ~ 50/60Hz 400W SERIAL NO.
MADE IN JAPAN	

SONY®	INTEGRATED STEREO AMPLIFIER MODEL NO. TA-F7B AC 240V ~ 50/60Hz 410W SERIAL NO.
MADE IN JAPAN	

SONY®	INTEGRATED STEREO AMPLIFIER MODEL NO. TA-F7B AC 220V ~ 50/60Hz 400W SERIAL NO.
MADE IN JAPAN	

SECTION 1 OUTLINE

1-1. CIRCUIT DESCRIPTION

1-1-1. Equalizing Amplifier

Refer to Fig. 1-1. The input signal from PHONO 1 or PHONO 2 goes to the gate G1 of the dual-FET differential amplifier Q101 and the feedback signal from the output goes to the gate G2. Q101 amplifies these two input signals, and its output signals at the drains D1 and D2 are in reversed phase. Q106 and D101 are the load of the differential amplifier and compose a current-mirror circuit. This current mirror makes the differential amplifier have more gain and less distortion by re-using the output current in other than the load of the differential amplifier and making it a load current. The output signal appeared in the drain D1 next goes to the base of Q107.

Q107 and Q108 compose a darlington circuit, and this circuit has a proper gain by having a constant-current source Q109. Q102 in the source return of the differential amplifier Q101 is a constant-current source and serves as an infinite impedance against the input signal to the differential amplifier. Transistor Q102 is used instead of a large resistor in this stage, because the dual FET Q101 is drawing a relatively large current from the limited B+ voltage to improve audio quality.

Q103 and Q104 compose a voltage regulator and the voltage V_0 , namely the base-bias of Q102, is maintained constant to make Q102 stable. The current I_1 which flows through the constant-current source Q102 is expressed as

$$I_1 \approx \frac{V_0 - V_{BE1}}{R106}$$

where $V_0 = V_{BE2} + V_1$

V_1 is determined by I_0 which flows through R112 by V_{BE2}

So, I_1 is determined by V_{BE1} and V_{BE2} and is independent upon B+ and B- voltages, namely I_1 is constant.

Furthermore, this equalizing amplifier is stabilized dc-current-wise by utilizing a dc feedback circuit of Q105 as well as the dependent feedback circuit to produce the RIAA deemphasis curve. Here, Q105 serves as a voltage follower and its dc gain G is determined as

$$G \approx \frac{R110}{R107} \approx 30 \text{ dB}$$

The lower-side cutoff frequency is determined by R116 and C107 in the gate circuit of Q105.

The RIAA curve to be used as a record amplifier is produced by the feedback components C105, C106, R108, R109, R120 and C109. And the output

signal is fed back to the gate G2 of Q101, thus making a voltage feedback loop.




Fig. 1-1.

1-1-2. Power Amplifier

(1) Class-A Amplifier

Refer to Fig. 1-2 and Fig. 1-3. The output signal from the preamplifier section goes to the gate G1 of the dual-FET differential amplifier Q605. The output signal of the class-B amplifier is fed through a feedback route back to the other gate G2 of Q605. These two input signals are amplified in Q605 and mutually reversed-phase output signals are obtained at its drains D1 and D2. Q603, Q604 and Q605 are composing a cascoded differential amplifier, and Q601 and Q602 are its load. Q601 and Q602 also compose a current-mirror circuit and of a push-pull configuration. By utilizing this current-mirror circuit, two outputs are compounded resulting in a high amplification with less distortion.

Due to the high-gain operation of the first stage, Q603 and Q604 lock the drain voltage V_D of Q605 and shift the level, and thus reducing noise component produced by the drain current. The locked drain voltage V_D is expressed as

$$V_D \cong V_{CC} \times \frac{R_{604}}{R_{603} + R_{604}} \cong 15 \text{ V}$$

The output signal at the drain of Q603 next goes to the class-A cascoded amplifier composed of Q607 and Q608 which has a constant-current load Q611. And its output signal is next applied to and voltage amplified by the following class-B amplifier.




Fig. 1-2.

These two cascoded amplifiers composed of Q603 to Q605, and of Q607 and Q608 are the combination of the common emitter (or source) and

common base (or gate) circuits. In these amplifiers, the mirror effect due to the feedback capacitor from the output side does not present, so they are increasing the transmission capability of high-frequency component. Furthermore, R607 and C602 are connected inbetween the drains of Q603 and Q604 of the first-stage cascoded differential amplifier to make the load impedance low at high frequency, and thus reducing the fluctuation of the amplifier gain.

(B) Class-B Amplifier

Refer to Fig. 1-3. These class-B amplifiers are cascode-type amplifiers utilizing features of the bipolar transistors and V-FETs, and they are improving the signal-transmission characteristics.

Q616 is a class-B driver and emitter follower followed by the final-stage power amplifier. The final-stage power amplifier is a pure-complementary circuit composed of cascode configuration of Q618, Q619 and Q901 to Q903.

When the bipolar transistors and V-FETs are connected in a cascode configuration, V_{CE} of the bipolar transistors Q618 and Q619 becomes the reversed bias of the gate of V-FET and this bias prevents V-FET from damaging, otherwise V-FET may be damaged by a huge current equivalent to I_{DSS} . This reversed bias of V-FET provides a good rejection characteristic against the fluctuation of the power supply voltage. In this configuration, the voltage applied to the bipolar transistor becomes as low as around 15 V and bipolar transistors with a high transition frequency f_T can be combined.




Fig. 1-3.

1-1-3. Power Supply

Refer to Fig. 1-4. This regulated power supply provides a power for the class-B amplifier. This voltage regulator uses a constant-current circuit Q706 in the base-bias circuit of the control transistors Q704 and Q705. And this voltage regulator provides a high input impedance, low output impedance and a good regulation against the fluctuation in the input voltage.




Fig. 1-4.

Fig. 1-5 shows the basic voltage-regulating circuit.




Fig. 1-5.

The voltage regulation factor is expressed as

$$\frac{\Delta V_o}{\Delta V_i} \approx \frac{R_d}{R_1 + R_d}$$

where, ΔV_o = fluctuation of output voltage

ΔV_i = fluctuation of input voltage

R_{d1} = active resistance of D1

Accordingly, on a constant R_{d1} , the larger R_1 the better a voltage regulation. In the circuit in Fig. 1-4, a good voltage regulation is obtained by utilizing an FET-type constant-current source and a large R_1 .

The output impedance of the circuit in Fig. 1-5 is expressed as

$$R_o \approx \frac{\Delta V_o}{\Delta I_o} \\ \approx \frac{R_b + R_d}{1 + h_{FE}}$$

where, R_b = base resistance of Q1


h_{FE} = current amplification factor of Q1

Therefore, a low output impedance is obtainable with a transistor having a large h_{FE} . So in the actual circuit in Fig. 1-4, a darlington configuration is used in the place of Q1 in Fig. 1-5 together with a large resistance R_1 .

To obtain a good rejection factor against the ripple component, a bootstrap circuit composed of R709 and D711 is used.




12. BLOCK DIAGRAM

Note: * The capacitor indicated by * is an only coupling capacitor in TONE OFF mode except for signal path from PHONO (1) and PHONO (2) to EQ amp output.




SECTION 2 DISASSEMBLY


Note: Remove in the numerical order.



POWER V-FET REPLACEMENT




CHECKING OF THE BOARD



SECTION 3 ADJUSTMENT

Note: 1. As outlined in the circuit description, this set uses bipolar transistors and V-FETs in cascode circuit to maintain stable biasing. When replacing the three P-channel V-FETs 2SK60 and/or the three N-channel V-FETs 2SJ18 in each channel, use three matched ones which have the same V_p (pinch-off voltage)-rank figure printed on them as shown below. The fluctuation of the V_p rank of the three can be acceptable on one-rank-difference basis.



- When the power transistors are replaced, be sure to perform the DC BIAS and DC BALANCE adjustments again.
- Perform DC BIAS and DC BALANCE adjustments a few minutes passed after POWER switch turned ON.
- Repeat DC BIAS and DC BALANCE adjustments a few times because they affect each other.


DC Balance Adjustment

- Connect a dc millivoltmeter to SPEAKER terminals.
- Turn POWER switch ON. Adjust RT601 (L-CH) and RT651 (R-CH) for 0V reading on the millivoltmeter.

Note:

When the controls are turned in the arrowed direction \times , voltage reading increases.


Same power-amp circuit boards are used in both L- and R-channels. Component reference numbers printed on the circuit board are different from the circuit and mounting diagrams.



DC Bias Adjustment

- Connect a VOM to the dc-bias check points.
- With no input signal, adjust RT602 (L-CH) and RT652 (R-CH) for 12 mV reading on VOM.

L-CH power amp board
(same as R-CH)



power amp board
(R-CH)


Power Meter Adjustment

Setting: ATTENUATOR control: maximum
HIGH FILTER switch: OFF
LOW FILTER switch: OFF
MONITOR switch: SOURCE
FUNCTION switch: TUNER


TONE controls: mechanical mid
BALANCE control: mechanical mid
MUTING switch: OFF

Procedure:

1.



- Adjust attenuator for 8.9V (10W) reading on VTVM.
- Adjust RT801 (L-CH) and RT851 (R-CH) so that power meters indicate 10W.



SECTION 4 DIAGRAMS


4-1. MOUNTING DIAGRAM (1) — Preamplifier Section —

CIRCUIT BOARD LOCATION


Replacement Semiconductors

For replacement, use semiconductors except in ().


Q101, 151: 2SK97




Q102-104
Q152-154
Q203, 205, 206
Q253, 255, 256 : 2SC1128




Q105, 155: 2SK43-2 (2SK43)
Q201, 202 : 2SK43-3A (2SK43)
Q251, 252 : 2SK43-3A (2SK43)




Q106, 107 : 2SA639S
Q156, 157 : 2SA639S
Q108, 158 : 2SA896
Q204, 254 : 2SA896



Q109, 159 : 2SC1811
Q207, 257 : 2SC1811




D101, 151: 1S1555




Note:


- Color code of sleeving over the end of the jacket.




- ⊗ : Through hole.
- ▨ : component-side pattern.
- : B+ pattern.
- : B- pattern.




MUTING SWITCH BOARD



FLAT AMP BOARD



PHONO INPUT BOARD




SECTION 4
DIAGRAMS

4-1. MOUNTING DIAGRAM (1) — Preamplifier Section — — Conductor Side —


Replacement Semiconductors

For replacement, use semiconductors except in ().


Q101, 151: 2SK97




Q102-104
Q152-154
Q203, 205, 206
Q253, 255, 256 : 2SC1128




Q105, 155: 2SK43-2 (2SK43)
Q201, 202 : 2SK43-3A (2SK43)
Q251, 252 :




Q106, 107 : 2SA639S
Q156, 157 :
Q108, 158 : 2SA896
Q204, 254 :



Q109, 159 : 2SC1811
Q207, 257 :




D101, 151: 1S1555







Note:


- Color code of sleeving over the end of the jacket.




- ⊗ : Through hole.
- ▨ : component-side pattern.
- ▤ : B+ pattern.
- ▥ : B- pattern.

CIRCUIT BOARD LOCATION









Replacement Semiconductors

For replacement, use semiconductors except in ().


Q401,451: 2SC1636




Q504, 554: 2SC1128




Q501,551: 2SK43-3A (2SK43)




Q505: 2SC1061




Q502, 552: 2SA896




Q507, 556, 558: 2SA899




Q503, 553: 2SC1811




Q509, 559: 2SK42-2 (2SK42)




Q506, 508, 557: (2SC945)




Q555: 2SA671



Q506, 508, 557: 2SC634A





D501,551: EQA01-07




Note:

- Color code of sleeving over the end of the jacket.



-  : B+ pattern.
- : B- pattern.






Note: The components identified by shading and Δ mark are critical for safety. Replace only with part number specified.


- Note:
- Components for right channel have same values as for left channel. Reference numbers are coded from.
 - All capacitors are in μF unless otherwise noted. $\text{pF} = \mu\text{F}$ 50WV or less are not indicated except for electrolytics.
 - All resistors are in ohms, $\frac{1}{2}\text{W}$ unless otherwise noted. $\text{k}\Omega = 1000\Omega$, $\text{M}\Omega = 1000\text{k}\Omega$
 - \square : fusible resistor.
 - 0% indicates component tolerance.
 - \blacksquare : B+ bus.
 - \blacksquare : B- bus.
 - \square : panel designation.
 - Readings are taken under no signal conditions with a VOM (20 $\text{k}\Omega/\text{V}$).
 - Switch


Ref. No.	Switch	Position
S1	FUNCTION (1)	FUNCTION (2)
S2	FUNCTION (2)	PHONO 2
S3	TAPE COPY	SOURCE
S4	MONITOR	SOURCE
S5	MODE	REVERSE
S6	MUTING	OFF
S7	TONE	OFF
S8	TURNOVER TREBLE	4 kHz
S9	TURNOVER BASS	300 Hz
S10	HIGH FILTER	OFF
S11	LOW FILTER	OFF

TA-F7/TA-F7B TA-F7/TA-F7B



4-5. SCHEMATIC DIAGRAM – Power Amplifier and Power Supply Sections –






Note: The components identified by shading and Δ mark are critical for safety. Replace only with part number specified.

- Note:
- Components for right channel have same values as for left channel. Reference numbers are coded from.
 - All capacitors are in μF unless otherwise noted. $\text{pF} = \mu\text{F} / 100$. 50WV or less are not indicated except for electrolytics.
 - All resistors are in ohms, $\frac{1}{4}\text{W}$ unless otherwise noted. $\text{k}\Omega = 1000\Omega$, $\text{M}\Omega = 1000\text{k}\Omega$.
 - Δ : nonflammable resistor.
 - \sim : fusible resistor.
 - --- : B+ bus.
 - --- : B- bus.
 - \square : panel designation.
 - \square : adjustment for repair.
 - Readings are taken under no signal conditions with a VOM (20 $\text{k}\Omega/\text{V}$).
 - Switch

Ref. No.	Switch	Position
S12	SPEAKER	OFF
S13	POWER	OFF


SECTION 5
EXPLODED VIEWS

A B C D E



- Note:
- Items with no part number and/or no description are not stocked because they are seldom required for routine service.
 - All screws are Phillips (cross recess) type unless otherwise noted.
 - (-) = slotted head
- Circled letters (A to Z) are applicable to European models only.

A B C D E



- Note:
- Items with no part number and/or no description are not stocked because they are seldom required for routine service.
 - All screws are Phillips (cross recess) type unless otherwise noted.
 - (-) = slotted head
- Circled letters (A to Z) are applicable to European models only.


Note: The components identified by shading and A mark are critical for safety. Replace only with part number specified.

A B C D E



(-) = slotted head

A B C D E




Note:


- Items with no part number and/or no description are not stocked because they are seldom required for routine service.
- All screws are Phillips (cross recess) type unless otherwise noted.

(-) = slotted head

- Circled letters (A to Z) are applicable to European models only.

Note: The components identified by shading and  mark are critical for safety. Replace only with part number specified.

A B C D E



Note:

- Items with no part number and/or no description are not stocked because they are seldom required for routine service.
- All screws are Phillips (cross recess) type unless otherwise noted.

(-) = slotted head

- Circled letters (A to Z) are applicable to European models only.

Note: The components identified by shading and  mark are critical for safety. Replace only with part number specified.

SECTION 6 ELECTRICAL PARTS LIST

• Circled letters (A to Z) are applicable to European models only.

Ref. No. Part No. Description

PRINTED CIRCUIT BOARD

1-585-589-12 (E) Power Amp

SEMICONDUCTORS

Transistors


Q101,151	(F) 2SK97
Q102-104	(C) 2SC1128
Q152-154	(C) 2SK43-2
⇒ Q105,155	(C) 2SA639S
Q106,107	
Q156,157	
Q108,158	(C) 2SA896
Q109,159	(C) 2SC1811
Q201,202	(F) 2SK43-3A
Q251,252	(C) 2SC1128
Q203,253	(C) 2SA896
Q204,254	(C) 2SC1128
Q205,206	(C) 2SC1128
Q255,256	(C) 2SC1811
Q207,257	
Q401,451	(B) 2SC1636
⇒ Q501,551	(F) 2SK43-3A
Q502,552	(C) 2SA896
Q503,553	(C) 2SC1811
Q504,554	(C) 2SC1128
Q505	(D) 2SC1061
Q555	(E) 2SA671
⇒ Q506	(B) 2SC634A
Q556	(C) 2SA899
Q507	(C) 2SA899
⇒ Q557	(B) 2SC634A
⇒ Q508	(B) 2SC634A
Q558	(C) 2SA899
⇒ Q509,559	(C) 2SK42-2
Q601,602	
Q651,652	(C) 2SA678

Ref. No. Part No. Description

⇒ Q603,604	(B) 2SK30A-GR
⇒ Q653,654	(F) 2SK97
Q605,655	(C) 2SC1128
Q606,656	(C) 2SA639S
Q607,657	
Q608,658	(C) 2SA896
Q609,659	(C) 2SC1128
Q610,660	(C) 2SC1811
Q611,661	(C) 2SA678
Q612,662	
Q613,663	(B) 2SC634A
Q614,664	(C) 2SA678
Q615,665	(C) 2SC1124
Q616,666	(D) 2SA706
Q617,667	
Q618,668	(C) 2SC1173
Q619,669	
Q620,670	(C) 2SA473
Q621,671	
Q701	(B) 2SC634A
Q702	(C) 2SA678
Q703	(B) 2SC634A
Q704	(D) 2SC1061
⇒ Q705	(B) 2SC634A
⇒ Q706	(C) 2SK42-2
Q707	(B) 2SC634A
Q708,709	(C) 2SA899
Q710	(E) 2SA671
⇒ Q711	(C) 2SK42-2
Q801,851	(B) 2SC634A
Q802,803	(C) 2SA678
Q901-903	(J) 2SK60
Q951-953	
Q904-906	(K) 2SJ18
Q954-956	
D101,151	(B) 1S1555

Diodes

• ⇒: Due to standardization, interchangeable replacements may be substituted for parts specified in the diagrams.



Note:

- Items with no part number and/or no description are not stocked because they are seldom required for routine service.
- All screws are Phillips (cross recess) type unless otherwise noted.
(-) = slotted head
- Circled letters (A to Z) are applicable to European models only.

Note: The components identified by shading and A mark are critical for safety. Replace only with part number specified.

SECTION 6
ELECTRICAL PARTS LIST

• Circled letters (A to Z) are applicable to European models only.

Ref. No.	Part No.	Description	Ref. No.	Part No.	Description
PRINTED CIRCUIT BOARD			⇒ Q603,604	ⓑ 2SK30A-GR	
1-585-589-12 ⓔ Power Amp			⇒ Q653,654	ⓕ 2SK97	
			Q605,655	Ⓒ 2SC1128	
			Q606,656	Ⓒ 2SA639S	
			Q607,657		
SEMICONDUCTORS			Q608,658	Ⓒ 2SA896	
Transistors			Q609,659	Ⓒ 2SC1128	
			Q610,660	Ⓒ 2SC1811	
Q101,151	ⓕ 2SK97		Q611,661	Ⓒ 2SA678	
Q102-104,	Ⓒ 2SC1128		Q612,662		
Q152-154			Q613,663	ⓑ 2SC634A	
⇒ Q105,155	Ⓒ 2SK43-2		Q614,664	Ⓒ 2SA678	
Q106,107,	Ⓒ 2SA639S		Q615,665	Ⓒ 2SC1124	
Q156,157			Q616,666	Ⓓ 2SA706	
Q108,158	Ⓒ 2SA896		Q617,667		
Q109,159	Ⓒ 2SC1811		Q618,668	Ⓒ 2SC1173	
Q201,202			Q619,669		
Q251,252	ⓕ 2SK43-3A		Q620,670	Ⓒ 2SA473	
Q203,253	Ⓒ 2SC1128		Q621,671		
Q204,254	Ⓒ 2SA896		Q701	ⓑ 2SC634A	
Q205,206	Ⓒ 2SC1128		Q702	Ⓒ 2SA678	
Q255,256	Ⓒ 2SC1811		Q703	ⓑ 2SC634A	
Q207,257			Q704	Ⓓ 2SC1061	
Q401,451	ⓑ 2SC1636		⇒ Q705	ⓑ 2SC634A	
⇒ Q501,551	ⓕ 2SK43-3A		⇒ Q706	Ⓒ 2SK42-2	
Q502,552	Ⓒ 2SA896		Q707	ⓑ 2SC634A	
Q503,553	Ⓒ 2SC1811		Q708,709	Ⓒ 2SA899	
Q504,554	Ⓒ 2SC1128		Q710	ⓔ 2SA671	
Q505	Ⓓ 2SC1061		⇒ Q711	Ⓒ 2SK42-2	
Q555	ⓔ 2SA671		Q801,851	ⓑ 2SC634A	
⇒ Q506	ⓑ 2SC634A		Q802,803	Ⓒ 2SA678	
Q556	Ⓒ 2SA899		Q901-903	ⓙ 2SK60	
Q507	Ⓒ 2SA899		Q951-953		
⇒ Q557	ⓑ 2SC634A		Q904-906	Ⓚ 2SJ18	
⇒ Q508	ⓑ 2SC634A		Q954-956		
Q558	Ⓒ 2SA899			Diodes	
⇒ Q509,559	Ⓒ 2SK42-2				
Q601,602			D101,151	ⓑ 1S1555	
Q651,652	Ⓒ 2SA678				

• ⇒: Due to standardization, interchangeable replacements may be substituted for parts specified in the diagrams.

Ref. No.	Part No.	Description
⇒ D501,551	ⓑ EQB01-07	
⇒ D601,651	Ⓒ KB462S	
D602,652	Ⓒ SV04S	
D603-606,	ⓑ 1S1555	
D653-656		
D701-706	ⓑ 10E2	
D707	ⓑ 1S1555	
⇒ D708	ⓑ 10E2	
⇒ D709,710	ⓑ EQB01-11Z	
⇒ D711,712	ⓑ EQB01-07	
D751,752	ⓕ S5VB20	

D801,851,	ⓑ 1T22M
D802,852	

THERMISTORS

Th801,851	1-800-202-XX	ⓐ Thermistor, S-10K
PTh1,2	1-800-427-00	ⓑ Thermistor

COILS

L401,451	1-407-879-00	ⓑ 33 mH, microinductor
L801,851	1-420-879-00	ⓑ Coil

TRANSFORMERS

PT1,2	1-442-941-11	ⓐ Power
PT3	1-442-942-11	ⓐ Power

CAPACITORS

All capacitors are in μ F and ceramic unless otherwise noted.
50 WV or less are not indicated except for electrolytics. pF = μ F, elect = electrolytic

C001,002	1-119-216-11	ⓑ 33 25V elect
C101,151	1-102-963-11	ⓐ 33p

⇒: Due to standardization, interchangeable replacements may be substituted for parts specified in the diagrams.

• Circled letters (A to Z) are applicable to European models only.

Ref. No.	Part No.	Description
C102,152	1-101-005-11	ⓐ 0.022
C103,153	1-102-973-11	ⓐ 100p
C104,154		
C105,155	1-130-131-11	ⓑ 1600p 100V polyethylene
C106,156	1-130-132-11	ⓑ 5600p 100V polyethylene
C107,157	1-131-217-11	ⓑ 2.2 35V tantalum
C108,158	1-102-959-11	ⓐ 22p
C109,159	1-130-122-11	ⓑ 1000p 100V polyethylene
C110,160	1-123-250-11	ⓑ 2.2 100V elect
C111,161		
C112,162	1-130-133-11	ⓑ 56000p 100V polyethylene
C201,251	1-102-971-11	ⓐ 82p
C202,252	1-102-824-11	ⓐ 470p
C203,253	1-131-295-11	Ⓒ 100 6.3V tantalum
C204,254		
C205,255	1-130-133-11	ⓑ 56000p 100V polyethylene
C208	1-108-227-12	ⓐ 0.001 mylar
C401,451	1-108-360-12	ⓐ 0.039 mylar
C402,452	1-108-364-12	ⓑ 0.18 mylar
C403,453	1-108-581-12	ⓑ 0.012 mylar
C404,454	1-108-254-12	ⓑ 0.22 mylar
C405,455		
C501,551	1-102-115-11	ⓐ 560p
C502,552	1-108-228-12	ⓐ 0.0015 mylar
C503,553		
C504,554	1-108-237-12	ⓐ 0.0068 mylar
C505,555		
C506,556	1-108-360-12	ⓐ 0.039 mylar
C507,557	1-108-364-12	ⓑ 0.18
C508,558	1-102-125-11	ⓐ 4700p
C509,559	1-131-239-11	ⓑ 6.8 35V tantalum
C510,560		
C511,561	1-130-083-11	Ⓒ 1 100V polyethylene
C514,564	1-121-411-11	ⓑ 47 50V elect
C517,567	1-130-086-11	ⓑ 0.47 100V polyethylene
C601,651	1-101-005-11	ⓐ 0.022
C602,652	1-102-963-11	ⓐ 33p
C603,653	1-101-361-11	ⓐ 150p
C604,654	1-102-934-11	ⓐ 1p
C605,655		

Note: The components identified by shading and ⓐ mark are critical for safety. Replace only with part number specified.

Note: Circled letters (A to Z) are applicable to European models only.

Note: Circled letters (A to Z) are applicable to European models only.

Ref. No.	Part No.	Description
C606,656	1-101-001-11	(A) 1000p
C607,657	1-102-973-11	(A) 100p
C608,658	1-101-001-11	(A) 1000p
C609,659	1-121-651-11	(A) 10 16V elect
C610,660		
C611,661	1-108-244-12	(A) 0.033 mylar
C701,702	1-123-261-11	(E) 2200 63V elect
C703,704	1-130-086-11	(B) 0.47 100V polyethylene
C705	1-123-183-11	(A) 10 50V elect
C706	1-123-250-11	(B) 2.2 100V elect
C707	1-121-726-11	(A) 0.47 50V elect
C708	1-121-419-11	(B) 220 6.3V elect
C712,717	1-121-421-11	(B) 220 16V elect
C713,718	1-121-738-11	(B) 10 50V elect
C751-754	1-130-084-11	(D) 2.2 100V polyethylene
C755,756	1-123-260-11	(P) 15000 71V elect
C801,851	1-102-824-11	(A) 470p
C802,852	1-121-391-11	(A) 1 50V elect
C803,853	1-108-355-12	(A) 0.0056 mylar
C805	1-121-424-11	(B) 470 6.3V elect
C806-808	1-121-726-11	(A) 0.47 50V elect
C901,951	1-119-372-11	1 100V elect
C902,952		

RESISTORS

All resistors are in ohms. Common 1/4W carbon resistors are omitted.
Check schematic diagram for values.

R101,151	1-244-914-11	(A) 51k	1/2W
R102,152	1-244-873-11	(A) 1k	1/2W
R103,153	1-244-864-11	(A) 430	1/2W
R104,154	1-244-909-11	(A) 33k	1/2W
R105,155	1-244-865-11	(A) 470	1/2W
R107,157	1-244-873-11	(A) 1k	1/2W
R108,158	1-214-172-11	(B) 47k	1/4W metal oxide
R109,159	1-214-473-11	(B) 576k	1/2W metal oxide
R116,166	1-244-945-11	(A) 1M	1/2W
R117,167	1-244-909-11	(A) 33k	1/2W
R118,168	1-244-873-11	(A) 1k	1/2W

Note: The components identified by shading and A mark are critical for safety. Replace only with part number specified.

Ref. No.	Part No.	Description
R120,170	1-244-873-11	(A) 1k 1/2W
R202,252	1-244-919-11	(A) 2k 1/2W
R203,253	1-244-945-11	(A) 1M 1/2W
R204,254	1-244-873-11	(A) 1k 1/2W
R205,255		
R206,256	1-244-905-11	(A) 22k 1/2W
R208,258	1-244-877-11	(A) 1.5k 1/2W
R209,259	1-244-897-11	(A) 10k 1/2W
R214,264	1-244-873-11	(A) 1k 1/2W
R219	1-244-881-11	(A) 2.2k 1/2W
R301,351		
R302,352	1-244-897-11	(A) 10k 1/2W
R509,559	1-244-873-11	(A) 1k 1/2W
R510,560	1-244-945-11	(A) 1M 1/2W
R511,561	1-244-893-11	(A) 6.8k 1/2W
R512,562	1-244-881-11	(A) 2.2k 1/2W
R513,563	1-244-897-11	(A) 10k 1/2W
R514,564	1-244-861-11	(A) 330 1/2W
R520,570	1-244-897-11	(A) 10k 1/2W
R521,571	1-244-856-11	(A) 200 1/2W
R524,574	1-212-869-11	(A) 33 1/4W fusible
R527,577	1-212-990-11	(A) 220 1/2W fusible
R601,651	1-244-873-11	(A) 1k 1/2W
R602,652	1-244-921-11	(A) 100k 1/2W
R605,655		
R606,656	1-244-873-11	(A) 1k 1/2W
R611,661	1-244-887-11	(A) 3.9k 1/2W
R612,662	1-244-921-11	(A) 100k 1/2W
R613,663		
R614,664	1-244-897-11	(A) 10k 1/2W
R615,665	1-244-921-11	(A) 100k 1/2W
R622,672	1-211-522-11	(A) 100 1/4W
R624,674	1-211-530-11	(A) 220 1/4W
R629,679	1-211-630-11	(A) 470 1/2W
R630-633		
R680-683	1-217-158-11	(A) 0.47 5W metal oxide
R634,684	1-217-481-11	(B) 10 1W fusible
R708	1-211-516-11	(A) 56 1/4W

Ref. No.	Part No.	Description
R711,717	1-211-409-11	(A) 10 1/8W
R713,720	1-244-897-11	(A) 10k 1/2W
R714,719	1-244-886-11	(A) 3.6k 1/2W
R751,752	1-244-913-11	(A) 47k 1/2W
R804,854	1-213-147-11	(A) 2.2k 1W metal oxide
R806,856		
R807,857	1-244-865-11	(A) 470 1/2W
R808,858	1-212-370-11	(A) 6.8 1W
R812	1-206-666-11	(A) 1.2k 2W metal oxide
R813,814	1-217-160-11	(A) 1 5W metal oxide
R901,951		
R902,952	1-211-522-11	(A) 100 1/4W
RT601,651	1-224-487-00	(B) 220 adjustable
RT602,652	1-224-661-00	(B) 47k adjustable
RT801,851	1-224-492-00	(B) 100k adjustable
RV201,251	2-224-987-00	(H) 100k, variable; ATTENUATOR
RV401,451	1-224-986-00	(E) 100k, variable; BALANCE
RV402,452	1-224-988-00	(H) 50k, variable; TREBLE
RV403,453	1-224-989-00	(H) 51k, variable; BASS

SWITCHES

S1	1-552-089-00	(E) Lever Slide, FUNCTION (1)
S2	1-552-182-00	(F) Rotary Slide, FUNCTION (2)
S3,4	1-552-032-00	(D) Lever Slide, TAPE COPY, MONITOR
S5	1-552-087-00	(F) Rotary, MODE
S6	1-552-031-00	(C) Lever Slide, MUTING
S7-9	1-552-090-00	(H) Lever Slide, TURNOVER (BASS, TREBLE)/TONE
S10,11	1-552-085-00	(D) Lever Slide, LOW FILTER, HIGH FILTER
S12	1-552-086-00	(F) Rotary, SPEAKER
S13	1-552-141-00	(E) Pushbutton, POWER

JACKS

J001	1-507-454-00	(C) HEADPHONES
J101,151		
J102,152	1-507-416-XX	(C) 4p, PHONO 1, PHONO 2
J103-105		
J153-155	1-507-430-XX	(D) 6p, TUNER, AUX 1, AUX 2

Note: The components identified by shading and A mark are critical for safety. Replace only with part number specified.

Ref. No.	Part No.	Description
J106-109		
J156-159	1-507-429-XX	(E) 8p, TAPE 1, TAPE 2 REC OUT 1, REC OUT 2
J110,160		
J111,161	1-507-470-00	(C) 4p, PRE/POWER
J501	1-507-453-00	(C) TAPE 2
J502	1-507-454-00	(C) REC OUT 2

CNJ	1-509-546-00	(D) 3p, socket; AC IN
-----	--------------	-----------------------

MISCELLANEOUS

CB801,802	1-532-531-11	(C) Circuit Breaker, 2A
CP701		
CP751,752	1-102-355-11	(B) Encapsulated Component
F801	1-532-496-11	(C) Fuse 10A
M801,851	1-520-291-00	(L) Meter, level
RY001,002	1-515-277-00	(F) Relay
RY801,802	1-515-257-00	(H) Relay (TA-F7)
	1-515-293-00	(H) Relay (TA-F7B)
RY803	1-515-278-00	(F) Relay
TM1,2	1-535-182-00	(F) Terminal Strip, 4p; SPEAKER A, B
	1-506-370-00	(B) Plug
	1-525-186-00	(B) Socket, transistor
	1-536-430-12	(B) Terminal Strip

ACCESSORIES & PACKING MATERIALS

Part No.	Description
1-506-113-00	(B) Short Plug
1-534-819-12	(G) Cord, power (UK model)
3-701-020-00	(A) Bag, SS check sheet
3-701-622-00	(A) Bag, plastic (UK model)
3-770-394-11	(K) Manual, instruction
4-848-648-00	(B) Bag, protection
4-848-659-00	(H) Carton (TA-F7)
4-848-664-00	(H) Carton (TA-F7B)
4-848-660-00	(D) Frame
4-848-661-00	(C) Cushion, lower
4-848-658-00	(C) Cushion, upper

Note: Circled letters (A to Z) are applicable to European models only.

HARDWARE NOMENCLATURE

Ref. No. Part No. Description

R711,717 A1-211-409-11 A 10 1/8W
R713,720 1-244-897-11 A 10k 1/2W
R714,719 1-244-886-11 A 3.6k 1/2W
R751,752 A1-244-913-11 A 47k 1/2W

R804,854 A1-213-147-11 A 2.2k 1W metal oxide
R806,856 A1-244-865-11 A 470 1/2W
R807,857 A1-212-370-11 A 6.8 1W
R808,858 A1-206-666-11 A 1.2k 2W metal oxide
R812 A1-217-160-11 A 1 5W metal oxide

R901,951 A1-211-522-11 A 100 1/4W
R902,952 A1-211-522-11 A 100 1/4W

RT601,651 1-224-487-00 B 220 adjustable
RT602,652 1-224-661-00 B 47k adjustable

RT801,851 1-224-492-00 B 100k adjustable

RV201,251 2-224-987-00 H 100k, variable; ATTENUATOR

RV401,451 1-224-986-00 E 100k, variable; BALANCE
RV402,452 1-224-988-00 H 50k, variable; TREBLE
RV403,453 1-224-989-00 H 51k, variable; BASS

SWITCHES

S1 1-552-089-00 E Lever Slide, FUNCTION (1)
S2 1-552-182-00 F Rotary Slide, FUNCTION (2)
S3,4 1-552-032-00 D Lever Slide, TAPE COPY, MONITOR
S5 1-552-087-00 F Rotary, MODE
S6 1-552-031-00 C Lever Slide, MUTING

S7-9 1-552-090-00 H Lever Slide, TURNOVER (BASS, TREBLE)/TONE

S10,11 1-552-085-00 D Lever Slide, LOW FILTER, HIGH FILTER

S12 1-552-086-00 F Rotary, SPEAKER
S13 A1-552-141-00 E Pushbutton, POWER

JACKS

J001 1-507-454-00 C HEADPHONES
J101,151 1-507-416-XX C 4p, PHONO 1, PHONO 2
J102,152 1-507-416-XX C 4p, PHONO 1, PHONO 2
J103-105 1-507-430-XX D 6p, TUNER, AUX 1, AUX 2
J153-155 1-507-430-XX D 6p, TUNER, AUX 1, AUX 2

Note: The components identified by shading and A mark are critical for safety. Replace only with part number specified.

Ref. No. Part No. Description

J106-109 1-507-429-XX E 8p, TAPE 1, TAPE 2
J156-159 1-507-429-XX E REC OUT 1, REC OUT 2
J110,160 1-507-470-00 C 4p, PRE/POWER
J111,161 1-507-470-00 C 4p, PRE/POWER

J501 1-507-453-00 C TAPE 2
J502 1-507-454-00 C REC OUT 2

CNJ A1-509-546-00 D 3p, socket; AC IN

MISCELLANEOUS

CB801,802 A1-532-531-11 C Circuit Breaker, 2A
CP701 A1-102-355-11 B Encapsulated Component
CP751,752 A1-102-355-11 B Encapsulated Component

F801 A1-532-496-11 C Fuse 10A

M801,851 1-520-291-00 L Meter, level

RY001,002 1-515-277-00 F Relay
RY801,802 1-515-257-00 H Relay (TA-F7)
1-515-293-00 H Relay (TA-F7B)
RY803 1-515-278-00 F Relay

TM1,2 1-535-182-00 F Terminal Strip, 4p; SPEAKER A, B

1-506-370-00 B Plug

1-525-186-00 B Socket, transistor

1-536-430-12 B Terminal Strip

ACCESSORIES & PACKING MATERIALS

Part No. Description
1-506-113-00 B Short Plug
1-534-819-12 G Cord, power (UK model)

3-701-020-00 A Bag, SS check sheet
3-701-622-00 A Bag, plastic (UK model)
3-770-394-11 K Manual, instruction

4-848-648-00 B Bag, protection
4-848-659-00 H Carton (TA-F7)
4-848-664-00 H Carton (TA-F7B)
4-848-660-00 D Frame
4-848-661-00 C Cushion, lower
4-848-658-00 C Cushion, upper

Screw:

P 3 x 10
L: Length in mm
D: Diameter in mm
Type of head

Indicated slotted-head only.

Unless otherwise indicated, it means cross-recessed head (Phillips type).

Nut, Washer, Retaining ring:

N 3
Diameter of usable screw or shaft
Reference designation

Reference Designation	Shape	Description	Remarks
SCREWS			
P		pan-head screw	binding-head (B) screw for replacement
PWH		pan-head screw with washer face	binding-head (B) screw and flat washer for replacement
PS PSP		pan-head screw with spring washer	binding-head (B) screw and spring washer for replacement
PSW PSPW		pan-head screw with spring and flat washers	binding-head (B) screw and spring and flat washers for replacement
R		round-head screw	binding-head (B) screw for replacement
K		flat-countersunk-head screw	
RK		oval-countersunk-head screw	
B		binding-head screw	
T		truss-head screw	binding-head (B) screw for replacement
F		flat-fillister-head screw	
RF		fillister-head screw	
BV		braizer-head screw	

Reference Designation	Shape	Description	Remarks
SELF-TAPPING SCREWS			
TA		self-tapping screw	ex: TA, P 3 x 10
PTP		pan-head self-tapping screw	binding-head self-tapping (TA, B) screw for replacement
PTPWH		pan-head self-tapping screw with washer face	binding-head self-tapping (TA, B) screw and flat washer for replacement
PTTWH		pan-head thread-rolling screw with washer face	binding-head (B) screw and flat washer for replacement
SET SCREWS			
SC		set screw	
SC		hexagon-socket set screw	ex: SC 2.6 x 4, hexagon socket
NUT			
N		nut	
WASHERS			
W		flat washer	
SW		spring washer	
LW		internal-tooth lock washer	ex: LW3, internal
LW		external-tooth lock washer	ex: LW3, external
RETAINING RINGS			
E		retaining ring	
G		grip-type retaining ring	

1/4 WATT CARBON RESISTORS (A)

Note: Circled letter (A) is applicable to European model only.

Ω	Part No.	Ω	Part No.	Ω	Part No.	Ω	Part No.	Ω	Part No.	Ω	Part No.	Ω	Part No.	Ω	Part No.
1.0	1-244-601-11	10	1-244-625-11	100	1-244-649-11	1.0k	1-244-673-11	10k	1-244-697-11	100k	1-244-721-11	1.0M	1-244-745-11		
1.1	1-244-602-11	11	1-244-626-11	110	1-244-650-11	1.1k	1-244-674-11	11k	1-244-698-11	110k	1-244-722-11	1.1M	1-244-746-11		
1.2	1-244-603-11	12	1-244-627-11	120	1-244-651-11	1.2k	1-244-675-11	12k	1-244-699-11	120k	1-244-723-11	1.2M	1-244-747-11		
1.3	1-244-604-11	13	1-244-628-11	130	1-244-652-11	1.3k	1-244-676-11	13k	1-244-700-11	130k	1-244-724-11	1.3M	1-244-748-11		
1.5	1-244-605-11	15	1-244-629-11	150	1-244-653-11	1.5k	1-244-677-11	15k	1-244-701-11	150k	1-244-725-11	1.5M	1-244-749-11		
1.6	1-244-606-11	16	1-244-630-11	160	1-244-654-11	1.6k	1-244-678-11	16k	1-244-702-11	160k	1-244-726-11	1.6M	1-244-750-11		
1.8	1-244-607-11	18	1-244-631-11	180	1-244-655-11	1.8k	1-244-679-11	18k	1-244-703-11	180k	1-244-727-11	1.8M	1-244-751-11		
2.0	1-244-608-11	20	1-244-632-11	200	1-244-656-11	2.0k	1-244-680-11	20k	1-244-704-11	200k	1-244-728-11	2.0M	1-244-752-11		
2.2	1-244-609-11	22	1-244-633-11	220	1-244-657-11	2.2k	1-244-681-11	22k	1-244-705-11	220k	1-244-729-11	2.2M	1-244-753-11		
2.4	1-244-610-11	24	1-244-634-11	240	1-244-658-11	2.4k	1-244-682-11	24k	1-244-706-11	240k	1-244-730-11	2.4M	1-244-754-11		
2.7	1-244-611-11	27	1-244-635-11	270	1-244-659-11	2.7k	1-244-683-11	27k	1-244-707-11	270k	1-244-731-11	2.7M	1-244-755-11		
3.0	1-244-612-11	30	1-244-636-11	300	1-244-660-11	3.0k	1-244-684-11	30k	1-244-708-11	300k	1-244-732-11	3.0M	1-244-756-11		
3.3	1-244-613-11	33	1-244-637-11	330	1-244-661-11	3.3k	1-244-685-11	33k	1-244-709-11	330k	1-244-733-11	3.3M	1-244-757-11		
3.6	1-244-614-11	36	1-244-638-11	360	1-244-662-11	3.6k	1-244-686-11	36k	1-244-710-11	360k	1-244-734-11	3.6M	1-244-758-11		
3.9	1-244-615-11	39	1-244-639-11	390	1-244-663-11	3.9k	1-244-687-11	39k	1-244-711-11	390k	1-244-735-11	3.9M	1-244-759-11		
4.3	1-244-616-11	43	1-244-640-11	430	1-244-664-11	4.3k	1-244-688-11	43k	1-244-712-11	430k	1-244-736-11	4.3M	1-244-760-11		
4.7	1-244-617-11	47	1-244-641-11	470	1-244-665-11	4.7k	1-244-689-11	47k	1-244-713-11	470k	1-244-737-11	4.7M	1-244-761-11		
5.1	1-244-618-11	51	1-244-642-11	510	1-244-666-11	5.1k	1-244-690-11	51k	1-244-714-11	510k	1-244-738-11	5.1M	1-244-762-11		
5.6	1-244-619-11	56	1-244-643-11	560	1-244-667-11	5.6k	1-244-691-11	56k	1-244-715-11	560k	1-244-739-11				
6.2	1-244-620-11	62	1-244-644-11	620	1-244-668-11	6.2k	1-244-692-11	62k	1-244-716-11	620k	1-244-740-11				
6.8	1-244-621-11	68	1-244-645-11	680	1-244-669-11	6.8k	1-244-693-11	68k	1-244-717-11	680k	1-244-741-11				
7.5	1-244-622-11	75	1-244-646-11	750	1-244-670-11	7.5k	1-244-694-11	75k	1-244-718-11	750k	1-244-742-11				
8.2	1-244-623-11	82	1-244-647-11	820	1-244-671-11	8.2k	1-244-695-11	82k	1-244-719-11	820k	1-244-743-11				
9.1	1-244-624-11	91	1-244-648-11	910	1-244-672-11	9.1k	1-244-696-11	91k	1-244-720-11	910k	1-244-744-11				

Sony Corporation

© 1978

— 32 —

9-958-464-01

78C0677-1
Printed in Japan